



VIZA.EX15345
Fittings, Grooved and Plain End

[Page Bottom](#)

Fittings, Grooved and Plain End

[See General Information for Fittings, Grooved and Plain End](#)

SMITH-COOPER INTERNATIONAL

EX15345

2867 VAIL AVE
 CITY OF COMMERCE, CA 90040 USA

The following fittings are intended for use with SMITH-COOPER INTERNATIONAL (EX15344) Listed rubber gasketed fittings.

Grooved End

Model	Type	Size In.	Rated Pressure (psig)
65E	90 Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3OD, 3, 4-1/4OD, 4, 5-1/4OD, 5-1/2 OD, 5, 6-1/4OD, 6-1/2OD, 6,	500
65E	90 Elbow	8	300
65AE	Adapter elbow groove x thread	1-1/4 x 0.5, 1.25 x 1, 2.5 x 0.5, 2.5 x 1	300
65DE	90 Elbow drain	2, 2-1/2, 3, 4, 5, 6,	300
65DE	90 Elbow drain	8	175
65ES	90° Elbow Short Radius	2, 2-1/2, 3, 4, 6,	300
65E	90 Elbow	10, 12	175
65F	45 Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3OD, 3, 4-1/4OD, 4, 5-1/4OD, 5-1/2 OD, 5, 6-1/4OD, 6-1/2OD, 6, 8	300
65F	45 Elbow	10, 12	175
65TT	22.5 Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3OD, 3, 4, 5-1/2OD, 6-1/2OD, 6, 8	300
65TT	22.5 Elbow	10, 12	175
65T	Tee	1-1/4, 1-1/2, 2, 2-1/2, 3OD, 3, 4-1/4OD, 4,5-1/4OD, 5-1/2 OD, 5, 6-1/4OD, 6-1/2OD,	500
65T	Tee	10, 12	175
65TS	Tee, short radius	2, 2-1/2,3, 4, 6	500
65RT	Reducing Tee	2x1-1/4, 1-1/2; 2-1/2x2; 3 ODx2; 3x2, 2-1/2, 3 OD; 4-1/4 ODx3 OD, 3; 4x2, 2-1/2, 3 OD, 3; 5-1/4 OD x 3 OD, 3, 4-1/4 OD, 4; 5-1/2 ODx2, 3 OD, 3, 4-1/4 OD, 4;;, 3 OD, 3;;, 3, 4-1/4 OD, 4, , 3, 4, 2-1/2, 3 OD, 3, 4-1/4 OD, 4, ,	500
65RT	Reducing Tee	6-1/4 ODx3 OD, 5-1/4 OD, 5-1/2 OD; 6-1/2 ODx3 OD,5-1/2 OD; 6x2, 2-1/2, 5-1/4 OD, 5, 5-1/2 OD; 8x4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD, 6	300
65RT	Reducing Tee	10x6-1/4OD, 6-1/2OD, 6, 8; 12x6-1/4OD, 6-1/2OD, 8, 10	175

65RT	Reducing Tee Threaded	3ODxG2; 3xG2, G2-1/2; 4xG2-1/2, G3; 6-1/2ODxG2-1/2, G3	300
65TM	Reducing Tee Threaded	3ODxG2; 3xG2, G2-1/2; 4xG2-1/2, G3; 6-1/2ODxG2-1/2, G3	300
65X	Cross	2, 3OD, 3,	500
65X	Cross	4	400
65X	Cross	4-1/4OD, 4, 5, 5-1/4OD, 5-1/2 OD, 6-1/4OD, 6-1/2OD, 6, 8	300
65X	Cross	10, 12	175
65C	Cap	1-1/4, 1-1/2, 2, 2-1/2, 3OD, 3, 4-1/4OD, 4, 5-1/4OD, 5-1/2 OD, 5, 6-1/4OD, 6-1/2OD, 6,	500
65C	Cap	8	300
65C	Cap	10, 12	175
65CR	Concentric Reducer	2x1-1/4, 1-1/2; 2-1/2x1-1/2, 2; 3 ODx1-1/4, 1-1/2, 2; 3x1-1/4, 1-1/2, 2, 2-1/2, 3 OD; 4-1/4 ODx3 OD, 3; 4x1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3; 5-1/4 ODx3 OD, 3, 4-1/4 OD, 4; 5-1/2 ODx2, 3 OD, 3, 4; 5x2, 2-1/2, 3, 4; 6-1/4 ODx3 OD, 3, 4-1/4 OD, 4, 5-1/4 OD, 5-1/2 OD; 6-1/2 ODx2, 3 OD, 3, 4, 5-1/2 OD; 6x2, 2-1/2, 3 OD, 3, 4-1/4 OD, 4, 5-1/4 OD, 5-1/2 OD, 5; 8x2-1/2, 3 OD, 3, 4-1/4 OD, 4, 5-1/4 OD, 5-1/2 OD, 5, 6-1/4 OD, 6	500
65CR	Concentric Reducer, Threaded	2xG1/2, G3/4, G1, G1-1/4, G1-1/2; 2-1/2xG1, G1-1/4, G1-1/2; 3 ODxG1/2, G3/4, G1, G1-1/4, G1-1/2, G2; 3xG1/2, G3/4, G1, G1-1/4, G1-1/2, G2, G2-1/2; 4-1/4 ODxG1, G1-1-1/4, G1-1/2, G2; 4xG1/2, G3/4, G1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 5-1/4ODxG1-1/4, G1-1/2, G2; 5-1/2 ODxG1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 5xG1, G1-1/4, G1-1/2; 6-1/4 ODxG1, G1-1/4, G1-1/2, G2; 6-1/2 ODxG1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 6xG1, G1-1/4, G1-1/2, G2, G2-1/2, 3; 8xG1, G1-1/4, G1-1/2, G2, G2-1/2, G3	300
65CR	Concentric Reducer	10x4-1/4OD, 4, 5-1/4OD, 5, 6-1/4OD, 6-1/2OD, 6, 8; 12x6-1/4OD, 6-1/2OD, 6, 8, 10	175
65DC	Drain Cap	2, 2-1/2, 3, 4, 5, 6	300
65DC	Drain Cap	8	175
65ER	Eccentric Reducer	3x2, 3OD; 4x3OD, 3; 6-1/2 ODx3OD; 6-1/2ODx3, 4; 8x4, 6-1/2 OD; 10x8;	300
65CF	Concentric Reducer, Threaded	2xG1/2, G3/4, G1, G1-1/4, G1-1/2; 2-1/2xG1, G1-1/4, G1-1/2; 3 ODxG1/2, G3/4, G1, G1-1/4, G1-1/2, G2; 3xG1/2, G3/4, G1, G1-1/4, G1-1/2, G2, G2-1/2; 4-1/4 ODxG1, G1-1-1/4, G1-1/2, G2; 4xG1/2, G3/4, G1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 5-1/4ODxG1-1/4, G1-1/2, G2; 5-1/2 ODxG1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 5xG1, G1-1/4, G1-1/2; 6-1/4 ODxG1, G1-1/4, G1-1/2, G2; 6-1/2 ODxG1, G1-1/4, G1-1/2, G2, G2-1/2, G3; 6xG1, G1-1/4, G1-1/2, G2, G2-1/2, 3; 8xG1, G1-1/4, G1-1/2, G2, G2-1/2, G3	300
65FA	Flange Adapter	2, 2-1/2, 3OD, 3, 4-1/4OD, 4, 5-1/4OD, 5-1/2 OD, 5, 6-1/4OD, 6-1/2OD, 6, 8	300
65FA	Flange Adapter	10, 12	175
65FA	Flange Adapter American Standard	2, 2-1/2, 3, 4, 5, 6, 8	300
65FA	Flange Adapter American Standard	10, 12	175
65EL	11.25° Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5,	500
65EL	11.25° Elbow	8	175

Last Updated on 2012-01-25

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".